



ADJUST UNDER FREQ
POT TO HALF WAY
BETWEEN CW & CCW

LETTER AFTER BACKSLASH IS
COLOR OF STRIPE. R = RED
W = WHITE Y = YELLOW
(WIRE LENGTH)
FABRCATED WIRES ARE 16 AWG
UNLESS OTHERWISE NOTED.

500:5 CURRENT TRANSFORMERS:
POWER GOES THRU WHITE WIRE
FIRST.

| | | | |
|--|--|---|--------------------|
| MATERIAL: | | BURRELL ENTERPRISES, INC. A TEXAS CORPORATION 972-475-8111 | |
| FINISH: | | | |
| DRAWN BY: BURRELL | | TITLE: 140 KW AC WIRING | |
| DATE: 02-27-07 | | REV. A | |
| TOLERANCES: .XX = ±.015 .XXX = ±.005 ANGLES: ±1' | | SIZE A | PART NO. 14EL-W002 |
| REMOVE ALL BURRS AND SHARP EDGES. | | POWDER COAT PAINT | |
| PART NUMBER FABRICATION TAG: (AS REQUIRED) → → → | | FABRICATE | WELD |
| | | PLATE | POWDER COAT PAINT |

| | | | | |
|--|------|----------------------------|------------------------|------|
| ECO# | REV. | DESCRIPTION | DATE | APP. |
| | A | CHANGED F- COLOR FROM PINK | 08-04-08 | BB |
| BEND RADIUS: | | BEND ALLOWANCE: | REQUIRED PER ASSEMBLY: | |
| PROPRIETARY DATA: This document contains proprietary information of BURRELL GENERATORS, INC. It is transmitted to you in confidence and trust and is to be returned upon request. Its contents may not be disclosed in whole or part or used for other than the purpose for which it is transmitted without the prior written permission of BURRELL GENERATORS, INC. | | | | |