



480 VOLT
OPTION

STANDARD
SINGLE/THREE
PHASE

10 GA ———
16 GA ———
UNLESS NOTED

MOTOR VOLTAGES:
60HZ
120-240 SINGLE PHASE = 240V
120-208 THREE PHASE = 208V
277-480 THREE PHASE = 240V
50HZ
220-380 THREE PHASE = 190V

ECO#	REV.	DESCRIPTION	DATE	APP.
	A	CHANGED T1 TO T2 ON 480 CONNECTION	05-01-07	BB
BEND RADIUS:		BEND ALLOWANCE:	REQUIRED PER ASSEMBLY:	

MATERIAL:		BURRELL ENTERPRISES, INC. A TEXAS CORPORATION 972-475-8111			
FINISH:					
DRAWN BY: BURRELL		TITLE: MOTOR WIRING			
DATE: 02-08-07					
TOLERANCES: .XX = ±.015 .XXX = ±.005 ANGLES = ±1'		SIZE A	PART NO. 14EL-W001	REV. A	
REMOVE ALL BURRS AND SHARP EDGES.		PART NUMBER FABRICATION TAG: (AS REQUIRED) → → →	FABRICATE -RW	WELD	PLATE
				POWDER COAT PAINT	

PROPRIETARY DATA: This document contains proprietary information of BURRELL GENERATORS, INC. It is transmitted to you in confidence and trust and is to be returned upon request. Its contents may not be disclosed in whole or part or used for other than the purpose for which it is transmitted without the prior written permission of BURRELL GENERATORS, INC.